
MonkeyType Documentation

Release 18.1.11

Matt Page & Carl Meyer

Jan 11, 2018

Contents

1	Example	3
2	Motivation	5
3	Requirements	7
4	Installing	9
5	How MonkeyType works	11
6	The Details	13
6.1	Configuration	13
6.2	Tracing function calls	16
6.3	Generating type annotations	18
6.4	Storing call traces	20
6.5	Frequently asked questions	22
7	Indices and tables	23
	Python Module Index	25

MonkeyType collects runtime types of function arguments and return values, and can automatically generate stub files or even add draft type annotations directly to your Python code based on the types collected at runtime.

CHAPTER 1

Example

Say `some/module.py` originally contains:

```
def add(a, b):  
    return a + b
```

And `myscript.py` contains:

```
from some.module import add  
  
add(1, 2)
```

Now we want to infer the type annotation of `add` in `some/module.py` by running `myscript.py` with MonkeyType. One way is to run:

```
$ monkeytype run myscript.py
```

By default this will dump call traces into a sqlite database in the file `monkeytype.sqlite3` in the current working directory. You can then use the `monkeytype` command to generate a stub file for a module, or apply the type annotations directly to your code.

Running `monkeytype stub some.module` will output a stub:

```
def add(a: int, b: int) -> int: ...
```

Running `monkeytype apply some.module` will modify `some/module.py` to:

```
def add(a: int, b: int) -> int:  
    return a + b
```

This example demonstrates both the value and the limitations of MonkeyType. With MonkeyType, it's very easy to add annotations that reflect the concrete types you use at runtime, but those annotations may not always match the full intended capability of the functions. For instance, `add` is capable of handling many more types than just integers. Similarly, MonkeyType may generate a concrete `List` annotation where an abstract `Sequence` or `Iterable` would be more appropriate. MonkeyType's annotations are an informative first draft, to be checked and corrected by a developer.

CHAPTER 2

Motivation

Readability and static analysis are the primary motivations for adding type annotations to code. It's already common in many Python style guides to document the argument and return types for a function in its docstring; annotations are a standardized way to provide this documentation, which also permits static analysis by a typechecker such as [mypy](#).

For more on the motivation and design of Python type annotations, see [PEP 483](#) and [PEP 484](#).

CHAPTER 3

Requirements

MonkeyType requires Python 3.6+ and the [retype](#) library (for applying type stubs to code files). It generates only Python 3 type annotations (no type comments).

CHAPTER 4

Installing

Install MonkeyType with `pip`:

```
pip install MonkeyType
```


CHAPTER 5

How MonkeyType works

MonkeyType uses the `sys.setprofile` hook provided by Python to interpose on function calls, function returns, and generator yields, and record the types of arguments / return values / yield values.

It generates `stub files` based on that data, and can use `retype` to apply those stub files directly to your code.

6.1 Configuration

Most of the useful ways to configure MonkeyType require writing Python code to implement your preferred behavior, so MonkeyType’s configuration is done in Python code. To customize MonkeyType, you:

1. subclass `monkeytype.config.Config` or `monkeytype.config.DefaultConfig`,
2. override one or more methods in your subclass,
3. instantiate your subclass, and
4. point MonkeyType to your custom `Config` instance.

Let’s look at those steps in more detail.

6.1.1 Subclassing Config or DefaultConfig

class `monkeytype.config.Config`

`Config` is the “empty” config; it’s not usable out of the box, and requires your subclass to fill in some blanks in order to get useful behavior. It has the following methods:

trace_store() → `CallTraceStore`

Return the `CallTraceStore` subclass you want to use to store your call traces.

This is the one method you must override if you subclass the empty `Config`.

trace_logger() → `CallTraceLogger`

Return the `CallTraceLogger` subclass you want to use to log your call traces.

If you don’t override, this returns an instance of `CallTraceStoreLogger` initialized with your `trace_store()`.

code_filter() → `CodeFilter`

Return the `code filter` that categorizes traced functions into ones you are interested in (so their traces should be stored) and ones you aren’t (their traces will be ignored).

If you don't override, returns `None`, meaning all traces will be stored. This will probably include a lot of standard-library and third-party functions!

sample_rate() → int

Return the integer sampling rate for your logged call traces. If you return an integer `N` from this method, `1/N` function calls will be traced and logged.

If you don't override, returns `None`, which disables sampling; all function calls will be traced and logged.

type_rewriter() → `TypeRewriter`

Return the `TypeRewriter` which will be applied to all your types when stubs are generated.

If you don't override, returns `NoOpRewriter`, which doesn't rewrite any types.

query_limit() → int

The maximum number of call traces to query from the trace store when generating stubs. If you have recorded a lot of traces, increasing this limit may improve stub accuracy, at the cost of slower stub generation.

On the other hand, if some of your recorded traces are out of date because the code has changed, and you haven't purged your trace store, increasing this limit could make stubs worse by including more outdated traces.

Defaults to 2000.

include_unparsable_defaults() → bool

In order to output complete and correct stubs, MonkeyType imports your code and inspects function signatures via the `inspect` standard library module, and then turns this introspected signature back into a code string when generating a stub.

Some function arguments may have complex default values whose `repr()` is not a valid Python expression. These cannot round-trip successfully through the introspection process, since importing your code does not give MonkeyType access to the original expression for the default value, as a string of Python code.

By default MonkeyType will simply exclude such functions from stub file output, in order to ensure a valid stub file. Return `True` from this config method to instead include these functions, invalid syntax and all; you'll have to manually fix them up before the stub file will be usable.

Defaults to `False`.

cli_context(command: str) → `Iterator[None]`

A context manager which wraps the execution of the CLI command.

MonkeyType has to import your code in order to generate stubs for it. In some cases, like if you're using Django, setup is required before your code can be imported. Use this method to define the necessary setup or teardown for your codebase.

This method must return a `context manager` instance. In most cases, the simplest way to do this will be with the `contextlib.contextmanager` decorator. For example, if you run MonkeyType against a Django codebase, you can setup Django before the command runs:

```
@contextmanager
def cli_context(self, command: str) -> Iterator[None]:
    import django
    django.setup()
    yield
```

`command` is the name of the command passed to the monkeytype cli: `'run'`, `'apply'`, etc.

The default implementation of this method returns a no-op context manager.

class monkeytype.config.DefaultConfig

DefaultConfig is the config MonkeyType uses if you don't provide your own; it's usable as-is, and you can inherit it if you just want to make some tweaks to the default setup. DefaultConfig overrides the following methods from *Config*:

trace_store() → SQLiteStore

Returns an instance of *SQLiteStore*, which stores call traces in a local SQLite database, by default in the file `monkeytype.sqlite3` in the current directory. You can override the path to the SQLite database by setting the `MT_DB_PATH` environment variable.

code_filter() → CodeFilter

Returns a predicate function that excludes code in the Python standard library and installed third-party packages from call trace logging.

type_rewriter() → ChainedRewriter

Returns an instance of *ChainedRewriter* initialized with the *RemoveEmptyContainers*, *RewriteConfigDict*, and *RewriteLargeUnion* type rewriters.

6.1.2 Using your custom config subclass

Once you've written a *Config* or *DefaultConfig* subclass, you need to instantiate it and point MonkeyType to that instance. The easiest way to do this is to create a file named `monkeytype_config.py` and create a *Config* instance in it named `CONFIG`; MonkeyType will find and use this config automatically.

For example, let's say you mostly like the default config, but you want to add a sampling rate, so you put this code in the file `monkeytype_config.py`:

```
from monkeytype.config import DefaultConfig

class MyConfig(DefaultConfig):
    def sample_rate(self):
        return 1000

CONFIG = MyConfig()
```

MonkeyType will automatically find and use this config (as long as `monkeytype_config.py` is on the Python path).

Specifying a config

You can also explicitly specify the config instance to use. For instance, when tracing calls using the `monkeytype.trace()` context manager, you can just pass your config object to it:

```
from monkeytype import trace
from some.module import my_config

with trace(my_config):
    # ... run some code you want to trace here ...
```

When running *the command line utility*, use the `--config` or `-c` option to point MonkeyType to your config, e.g.:

```
$ monkeytype -c some.module:my_config stub some.module
```

6.2 Tracing function calls

The core data type in MonkeyType is the `CallTrace`. A `CallTrace` instance represents a single traced call of a single function or method, including the concrete type of each argument and the return or yield type.

A `CallTrace` is recorded by `monkeytype run` or the `trace()` context manager (or direct use of a `CallTracer`), logged via a `CallTraceLogger`, probably stored in a `CallTraceStore`, and later queried from that store by `monkeytype stub` or `monkeytype apply` and combined with all other traces of the same function in order to generate a stub or type annotation for that function.

6.2.1 monkeytype run

The simplest way to trace some function calls with MonkeyType is to run a Python script under MonkeyType tracing using `monkeytype run` or `monkeytype run -m` at the command line:

```
$ monkeytype run myscript.py
$ monkeytype run -m mymodule
```

`monkeytype run` accepts the same `monkeytype -c` option as `monkeytype stub` and `monkeytype apply`, to point MonkeyType to the config it should use.

Because of the way Python treats scripts and imported modules differently, MonkeyType will not record traces for the entry point itself (that is, the script passed to `monkeytype run` or the module passed to `run -m`); traces are recorded only for imported modules. If you want to annotate the entry point script/module, write another short script that imports and calls its function(s), and run that script with `monkeytype run`.

6.2.2 trace context manager

You can also trace calls by wrapping a section of code inside the `trace()` context manager:

```
import monkeytype

with monkeytype.trace():
    # argument and yield/return types for all function calls will be traced
    # and stored to `monkeytype.sqlite3`
```

You can pass a `Config` object to `trace()` to customize its behavior:

```
import monkeytype
from my_mt_config import my_config

with monkeytype.trace(my_config):
    # arg and yield/return types for function calls here will be traced and
    # logged as specified by your config.
```

`monkeytype.trace([config: Config]) → ContextManager`

Trace all enclosed function calls and log them per the given `config`. If no `config` is given, use the `DefaultConfig`.

6.2.3 CallTracer

```
class monkeytype.tracing.CallTracer(logger: CallTraceLogger, code_filter: CodeFilter, sample_rate: int)
```

For more complex tracing cases where you can't easily wrap the code to trace in a context manager, you can also use a `CallTracer` directly. `CallTracer` doesn't accept a `Config` object; instead you pass it a logger, filter, and sample rate.

If you have a config, you can easily pull those from it:

```
from monkeytype.tracing import CallTracer
from my_mt_config import my_config

logger = my_config.trace_logger()
tracer = CallTracer(
    logger=logger,
    code_filter=my_config.code_filter(),
    sample_rate=my_config.sample_rate(),
)
```

The `CallTracer` has no public API apart from its constructor, but it is suitable for passing to `sys.setprofile` as a profiler:

```
sys.setprofile(tracer)

# run some code to be traced

sys.setprofile(None) # remove the tracer
```

If your `CallTraceLogger` requires flushing, you should also do this after completing tracing:

```
logger.flush()
```

6.2.4 Deciding which calls to trace

You probably don't want to store traces for every single function called by your program; that will likely include a lot of calls to Python standard-library or third-party library functions that aren't your target for type annotation.

To filter the calls that will be traced, you can return a predicate function from the `code_filter()` method of your `Config()`. This function should take a `Python code object` and return a boolean: `True` means the function will be traced, and `False` means it will not.

The `DefaultConfig` includes a code filter that excludes code from the Python standard library and site-packages (where third-party packages are installed).

6.2.5 Logging traces

A call-trace logger is responsible for accepting `CallTrace` instances one by one as they are generated by the tracing code and doing something with them. It could print them directly to stdout, in the simplest case, or (more likely) hand them off to a `CallTraceStore` for storage and later retrieval.

class `monkeytype.tracing.CallTraceLogger`

Defines the interface that call-trace loggers should implement.

log (*trace: CallTrace*) → None

Accept a single `CallTrace` and do something with it. This method is called every time a new `CallTrace` is generated.

flush () → None

Flush logged call traces. This method is called once on exiting from the `trace()` context manager.

This method doesn't have to be implemented; by default it is a no-op. For very simple trace loggers (e.g. logging to stdout), each trace can be fully handled in `log()` directly as it is received, and no batching or flushing is needed.

CallTraceStoreLogger

```
class monkeytype.db.base.CallTraceStoreLogger(store: CallTraceStore)
```

The typical function of a call-trace logger is just to batch collected traces and then store them in a `CallTraceStore`. This is implemented by `CallTraceStoreLogger`. Its `log()` method just appends the trace to an in-memory list, and its `flush()` method saves all collected traces to the given store.

CallTrace

```
class monkeytype.tracing.CallTrace(func: Callable, arg_types: Dict[str, type], return_type:
                                Optional[type] = None, yield_type: Optional[type] =
                                None)
```

Type information for one traced call of one function.

func: Callable

The function that was called.

funcname: str

Fully-qualified name of the function, including module name (e.g. `some.module.some_func` or `some.module.SomeClass.some_method`).

arg_types: Dict[str, type]

Dictionary mapping argument names to types, for this particular traced call.

return_type: Optional[type]

Type returned by this call, or `None` if this call did not return.

yield_type: Optional[type]

Type yielded by this call, or `None` if this call did not yield.

6.3 Generating type annotations

Use the `monkeytype` command-line script to generate and apply stub files based on recorded call traces.

The script must be able to import your code. It automatically adds the current working directory to the Python path, so ensuring that you run `monkeytype` from the root of your code is usually sufficient. Alternatively, you can set the `PYTHONPATH` environment variable.

6.3.1 monkeytype stub

Run `monkeytype stub some.module` to generate a stub file for the given module based on call traces queried from the trace store. If the module already has some type annotations, those annotations will be respected and will not be replaced with annotations derived from traced calls.

The generated stub file will be printed to standard output. If you want to save it to a file, redirect the output to a file (e.g. `monkeytype stub some.module > some/module.pyi`).

You can also run e.g. `monkeytype stub some.module:SomeClass` or `monkeytype stub some.module:somefunc` to generate a stub for just one class or function.

6.3.2 monkeytype apply

If you prefer inline type annotations, `monkeytype apply some.module` will generate annotations for `some.module` internally (in exactly the same way as `monkeytype stub` would), but rather than printing the annotations in stub syntax, it will apply them directly to the code file, modifying it in-place.

Obviously this is best used when the file is tracked in a version-control system, so you can easily see the changes made by MonkeyType and accept or reject them. MonkeyType annotations are rarely suitable exactly as generated; they are a starting point and usually require some adjustment by someone who understands the code.

6.3.3 Options

Both `monkeytype stub` and `monkeytype apply` accept the same set of options:

-c <config-path>, **--config** <config-path>

The location of the *config object* defining your call-trace store and other configuration. The config-path should take the form `some.module:name`, where `name` is the variable in `some.module` containing your config instance.

Optionally, the value can also include a `()` suffix, and MonkeyType will call/instantiate the imported function/class with no arguments to get the actual config instance.

The default value is `monkeytype.config:get_default_config()`, which tries the config path `monkeytype_config:CONFIG` and falls back to `monkeytype.config:DefaultConfig()` if there is no `monkeytype_config` module. This allows creating a custom config that will be used by default just by creating `monkeytype_config.py` with a `CONFIG` instance in it.

-l <limit>, **--limit** <limit>

The maximum number of call traces to query from your call trace store.

See the `query_limit()` config method.

Default: 2000

--disable-type-rewriting

Don't apply your configured *Type rewriters* to the output types.

--include-unparsable-defaults

Include stubs for functions with argument defaults whose reprs are not valid Python syntax.

See the `include_unparsable_defaults()` config method.

--exclude-unparsable-defaults

Exclude stubs for functions with argument defaults whose reprs are not valid Python syntax.

See the `include_unparsable_defaults()` config method.

6.3.4 Type rewriters

MonkeyType's built-in type generation is quite simple: it just makes a `Union` of all the types seen in traces for a given argument or return value, and shrinks that `Union` to remove redundancy. All additional type transformations are performed through configured type rewriters.

class `monkeytype.typing.TypeRewriter`

The *TypeRewriter* class provides a type-visitor that can be subclassed to easily implement custom type transformations.

Subclasses can implement arbitrary `rewrite_Foo` methods for rewriting a type named `Foo`. *TypeRewriter* itself implements only `rewrite_Dict`, `rewrite_List`, `rewrite_Set`,

`rewrite_Tuple`, `rewrite_Union` (in addition to the methods listed below). These methods just recursively rewrite all type arguments of the container types.

For example type rewriter implementations, see the source code of the subclasses listed below.

`rewrite` (*typ: type*) → type

Public entry point to rewrite given type; return rewritten type.

`generic_rewrite` (*typ: type*) → type

Fallback method when no specific `rewrite_Foo` method is available for a visited type.

`class monkeytype.typing.RemoveEmptyContainers`

Rewrites e.g. `Union[List[Any], List[int]]` to `List[int]`. The former type frequently occurs when a method that takes `List[int]` also sometimes receives the empty list, which will be typed as `List[Any]`.

`class monkeytype.typing.RewriteConfigDict`

Takes a generated type like `Union[Dict[K, V1], Dict[K, V2]]` and rewrites it to `Dict[K, Union[V1, V2]]`.

`class monkeytype.typing.RewriteLargeUnion` (*max_union_len: int = 5*)

Rewrites large unions (by default, more than 5 elements) to simply `Any`, for better readability of functions that aren't well suited to static typing.

`class monkeytype.typing.ChainedRewriter` (*rewriters: Iterable[TypeRewriter]*)

Accepts a list of rewriter instances and applies each in order. Useful for composing rewriters, since the `type_rewriter` config method only allows returning a single rewriter.

`class monkeytype.typing.NoOpRewriter`

Does nothing. The default type rewriter in the base `Config`.

6.4 Storing call traces

MonkeyType operates in two phases: *call tracing* and *stub generation*. You first run some code under MonkeyType tracing and store the traced calls. You can do this repeatedly, maybe even sampled in production continually so you always have up-to-date traces available. Then whenever you need, you run `monkeytype stub` or `monkeytype apply` to generate annotations based on types from the recorded traces.

In order to do this, MonkeyType needs a backing store for the recorded call traces. By default it will use `SQLiteStore`, which stores traces in a local SQLite database file. But you can write your own `CallTraceStore` subclass to store traces in whatever data store works best for you, and return an instance of your custom store from the `trace_store()` method of your `Config` class.

6.4.1 CallTraceStore interface

The `CallTraceStore` base class defines the interface that all call-trace stores must implement. The `SQLiteStore` subclass provides a useful example implementation of the `CallTraceStore` interface.

`class monkeytype.db.base.CallTraceStore`

`classmethod make_store` (*connection_string: str*) → `CallTraceStore`

Create and return an instance of the store, given a connection string.

The format and interpretation of the connection string is entirely up to the store class. Typically it might be e.g. a URI like `mysql://john:pass@localhost:3306/my_db`.

add (*traces: Iterable[CallTrace]*) → None
 Store one or more `CallTrace` instances.

Implementations of this method will probably find the `serialize_traces()` function useful.

filter (*module: str, qualname_prefix: Optional[str] = None, limit: int = 2000*) → List[`CallTraceThunk`]
 Query call traces from the call trace store. The `module` argument should be provided as a dotted Python import path (e.g. `some.module`).

The store should return the most recent `limit` traces available for the given `module` and `qualname`.

The returned `CallTraceThunk` instances can be any object that implements a `to_trace()` zero-argument method returning a `CallTrace` instance. This allows callers of `filter` to handle deserialization errors as desired per-trace.

Most stores will choose to return instances of `CallTraceRow`, which implements a `to_trace()` that deserializes traces from the same JSON format that its `from_trace()` classmethod serializes to.

6.4.2 SQLiteStore

MonkeyType bundles one sample store implementation, which `DefaultConfig` uses as the default store. It stores call traces in a SQLite database in a local file.

class monkeytype.db.sqlite.SQLiteStore

classmethod `make_store` (*connection_string: str*) → SQLiteStore
 The `connection_string` argument will be passed straight through to the Python standard library `sqlite` module.

add (*traces: Iterable[CallTrace]*) → None
 Store one or more `CallTrace` instances in the SQLite database, encoded via `CallTraceRow`.

filter (*module: str, qualname_prefix: Optional[str] = None, limit: int = 2000*) → List[`CallTraceRow`]
 Query up to `limit` call traces from the SQLite database for a given `module` and optional `qualname_prefix`, returning each as a `CallTraceRow` instance.

6.4.3 serialize_traces

`monkeytype.encoding.serialize_traces` (*traces: Iterable[CallTrace]*) → Iterable[`CallTraceRow`]
 Serialize an iterable of `CallTrace` to an iterable of `CallTraceRow` (via `CallTraceRow.from_trace()`). If any trace fails to serialize, the exception is logged and serialization continues.

6.4.4 CallTraceRow

The `CallTraceRow` class implements serialization/deserialization of `CallTrace` instances to/from JSON. See the implementation of `SQLiteStore` for example usage.

It is not required for a custom store to use `CallTraceRow`; a store may choose to implement its own alternative (de)serialization.

class monkeytype.encoding.CallTraceRow

classmethod `from_trace` (*trace: CallTrace*) → `CallTraceRow`
 Serialize a `CallTraceRow` from the given `CallTrace`.

to_trace() → *CallTrace*

Deserialize and return the *CallTrace* represented by this *CallTraceRow*.

module: *str*

The module in which the traced function is defined, e.g. `some.module`.

qualname: *str*

The `__qualname__` of the traced function or method, e.g. `some_func` for a top-level function or `SomeClass.some_method` for a method.

arg_types: *str*

A JSON-serialized representation of the concrete argument types for a single traced call. See the implementation for details of the format.

return_type: *Optional[str]*

A JSON-serialized representation of the actual return type of this traced call, or `None` if this call did not return (i.e. yielded instead).

yield_type: *Optional[str]*

A JSON-serialized representation of the actual yield type for this traced call, or `None` if this call did not yield (i.e. returned instead).

6.4.5 CallTraceThunk

The minimal required interface of the objects returned from *CallTraceStore.filter()*. Most stores will use *CallTraceRow* to satisfy this interface.

class `monkeytype.db.base.CallTraceThunk`

to_trace() → *CallTrace*

Produce a *CallTrace* instance based on the serialized trace data stored in this thunk.

6.5 Frequently asked questions

6.5.1 I'm using Django 1.11+ and monkeytype run manage.py test generates no traces.

Django 1.11 enabled parallel test runs by default. This means your tests run in separate subprocesses; MonkeyType is tracing only the main supervisor process, which runs only Django code (that is excluded from tracing by the default code filter). To get traces, use `--parallel 1` when running your tests under MonkeyType tracing.

6.5.2 I'm using Django, and I get an AppRegistryNotReady exception when I run monkeytype.

You need to use the *cli_context()* config method to call `django.setup()`.

6.5.3 Why did my test coverage measurement stop working?

MonkeyType uses the same `sys.setprofile` hook that `coverage.py` uses to measure Python code coverage, so you can't use MonkeyType and coverage measurement together. If you want to run your tests under MonkeyType tracing, disable coverage measurement for that run, and vice versa.

CHAPTER 7

Indices and tables

- `genindex`
- `modindex`
- `search`

m

- `monkeytype`, [16](#)
- `monkeytype.config`, [13](#)
- `monkeytype.db.base`, [20](#)
- `monkeytype.db.sqlite`, [21](#)
- `monkeytype.encoding`, [21](#)
- `monkeytype.tracing`, [15](#)
- `monkeytype.typing`, [19](#)

Symbols

-disable-type-rewriting
 monkeytype command line option, 19
 -exclude-unparsable-defaults
 monkeytype command line option, 19
 -include-unparsable-defaults
 monkeytype command line option, 19
 -c <config-path>, -config <config-path>
 monkeytype command line option, 19
 -l <limit>, -limit <limit>
 monkeytype command line option, 19

A

add() (monkeytype.db.base.CallTraceStore method), 20
 add() (monkeytype.db.sqlite.SQLiteStore method), 21

C

CallTrace (class in monkeytype.tracing), 18
 CallTraceLogger (class in monkeytype.tracing), 17
 CallTracer (class in monkeytype.tracing), 16
 CallTraceRow (class in monkeytype.encoding), 21
 CallTraceStore (class in monkeytype.db.base), 20
 CallTraceStoreLogger (class in monkeytype.db.base), 18
 CallTraceThunk (class in monkeytype.db.base), 22
 ChainedRewriter (class in monkeytype.typing), 20
 cli_context() (monkeytype.config.Config method), 14
 code_filter() (monkeytype.config.Config method), 13
 code_filter() (monkeytype.config.DefaultConfig method), 15
 Config (class in monkeytype.config), 13

D

DefaultConfig (class in monkeytype.config), 14

F

filter() (monkeytype.db.base.CallTraceStore method), 21
 filter() (monkeytype.db.sqlite.SQLiteStore method), 21
 flush() (monkeytype.tracing.CallTraceLogger method), 17

from_trace() (monkeytype.encoding.CallTraceRow class method), 21

G

generic_rewrite() (monkeytype.typing.TypeRewriter method), 20

I

include_unparsable_defaults() (monkeytype.config.Config method), 14

L

log() (monkeytype.tracing.CallTraceLogger method), 17

M

make_store() (monkeytype.db.base.CallTraceStore class method), 20
 make_store() (monkeytype.db.sqlite.SQLiteStore class method), 21
 monkeytype (module), 16
 monkeytype command line option
 -disable-type-rewriting, 19
 -exclude-unparsable-defaults, 19
 -include-unparsable-defaults, 19
 -c <config-path>, -config <config-path>, 19
 -l <limit>, -limit <limit>, 19
 monkeytype.config (module), 13
 monkeytype.db.base (module), 20
 monkeytype.db.sqlite (module), 21
 monkeytype.encoding (module), 21
 monkeytype.tracing (module), 15
 monkeytype.typing (module), 19

N

NoOpRewriter (class in monkeytype.typing), 20

P

Python Enhancement Proposals
 PEP 483, 5

PEP 484, [5](#)

Q

`query_limit()` (`monkeytype.config.Config` method), [14](#)

R

`RemoveEmptyContainers` (class in `monkeytype.typing`), [20](#)

`rewrite()` (`monkeytype.typing.TypeRewriter` method), [20](#)

`RewriteConfigDict` (class in `monkeytype.typing`), [20](#)

`RewriteLargeUnion` (class in `monkeytype.typing`), [20](#)

S

`sample_rate()` (`monkeytype.config.Config` method), [14](#)

`serialize_traces()` (in module `monkeytype.encoding`), [21](#)

`SQLiteStore` (class in `monkeytype.db.sqlite`), [21](#)

T

`to_trace()` (`monkeytype.db.base.CallTraceThunk` method), [22](#)

`to_trace()` (`monkeytype.encoding.CallTraceRow` method), [21](#)

`trace()` (in module `monkeytype`), [16](#)

`trace_logger()` (`monkeytype.config.Config` method), [13](#)

`trace_store()` (`monkeytype.config.Config` method), [13](#)

`trace_store()` (`monkeytype.config.DefaultConfig` method), [15](#)

`type_rewriter()` (`monkeytype.config.Config` method), [14](#)

`type_rewriter()` (`monkeytype.config.DefaultConfig` method), [15](#)

`TypeRewriter` (class in `monkeytype.typing`), [19](#)